

9" [T V S]

MONO MONITOR

Streamlined Appearance Designing

Ergonomics User Friendly

Flat Screen Dark-Tinted

Extremely Fine Definition

Universal Power Supply

Complied With EMI & Safety Standard




TM-9AF



TVS
MONITOR MFG & EXPORTER

TRY TVS AND YOU'LL BE SURE

A Picture is Worth a Thousand Words
A Perfect Screen is Worth a TVS Monitor



VM-9AF
VM-9DF

APPLICATION

- * Banking Systems
- * Point of Sales POS
- * Cash Dispenser ATM
- * Book-size IBM PC
- * Industrial Numeric Control Machine
- * Sub-Note Book
- * Limited User Space



MS-936D

9" MONOCHROME MONITOR SPECIFICATION

MODEL		VM-9AF / TM-9AF	VM-9DF
CRT	SIZE AND DEFLECTION PHOSPHOR	9" 90° NON-GLARE P/W, AMBER, GREEN.	9" 90° NON-GLARE P/W, AMBER, GREEN.
SYNC INPUT	H. SCAN FREQ. V. SCAN FREQ.	SEPARATE TTL LEVEL 30-38 KHz 50-90 Hz	TTL VIDEO 15.75/18.432 KHz 49 Hz / 60 Hz
VIDEO INPUT TYPE		ANALOG	TTL VIDEO / RGB INTENSITY
VIDEO BANDWIDTH		45 MHz ± 3db	22 MHz ± 3db
INPUT CONNECTOR		15 PIN, " D " TYPE	9 PIN, " D " TYPE
DISPLAY COLORS OR SHADES		UNLIMITED COLORS	8/16 SHADES
DISPLAY AREA	H x V	165 x 120 (±4 mm)	165 x 120 (±4 mm)
RESOLUTION		1024 x 768, 640 x 350, 640 x 400, 640 x 480, 800 x 600	720 x 348, 640 x 200
USER CONTROL	FRONT REAR	BRIGHT, CONTRAST, POWER SW. V-SIZE, H-PHASE SUB-BRIGHT, FOCUS	BRIGHT, CONTRAST, POWER SW. V-SIZE, H-PHASE SUB-BRIGHT, FOCUS
APPLICATION		POS, BANKING SYSTEM, FILE SEVER, BOOK SIZE PC, IBM PC.	
POWER INPUT		AC 100V ~ 240V, 50/60 Hz	AC 100V ~ 240V, 50/60 Hz
POWER CONSUMPTION		MAX. 35W	MAX. 30W
COMPATIBILITY		VGA, SVGA	MDA, CGA
PHYSICAL DIMENSION	W x H x D	236 x 233 x 246 mm	236 x 233 x 246 mm
PACKING DIMENSION	W x H x D	305 x 305 x 305 mm	305 x 305 x 305 mm
NET WEIGHT		3.5 Kgs	3.5 Kgs
GROSS WEIGHT		4.5 Kgs	4.5 Kgs
SAFETY	(OPTIONAL)	UL, CSA, TÜV, CE, FDA	NONE
EMI	(OPTIONAL)	FCC-B, CE, BCIQ	FCC-A, BCIQ

* Specifications subject to change without notice.

* All trademarks are the property of their owners.

