

KX-P1131 Dot Matrix Printer



Features:

- 300 cps Draft Micron and 80 cps Letter Quality
- 6 internal scalable fonts, ranging 8 to 32 points
- 10 resident bitmap fonts (3 Draft & 7 LQ), available in nine character sizes ranging from 5-20 cpi plus proportional setting
- Rear & Top feeds give you a wide choice of paper paths
- Paper Parking (Memo load)---
- Load single sheets without removing or wasting continuous forms
- Perforated cut with 0 tear off capability---
- Maximize printable area without wasting any paper forms
- Top of Form function (TOF SET)
- Serial and Parallel Interface and Selectable Buffer (1KB/8KB/22KB (default)/54KB)
- Set-up diskette includes Windows™ 3.1/95/98 drivers
- New long type ribbon gives you a 6 million character life

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1999 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

	Panasonic Digital Imaging Company Unit of Matsushita Electric Corporation of America Computer Peripherals Division Headquarters: 2 Panasonic Way, Secaucus, NJ 07094
--	---

www.panasonic.com/office

KX-P1131 Specifications

Print Process	Impact Serial Dot Matrix	
Printhead and Life	24-pin (0.2 mm wire diameter), 200 million strokes; (100 million characters in draft mode)	
Print Direction	Logic Seeking Bi-Directional Character	
Print Speed (characters per sec)		Draft LQ
	Micron	300 cps 100 cps
	Elite	240 cps 80 cps
	Pica	200 cps 66 cps
Letter Quality Fonts	Courier, Bold PS, Roman, Sans Serif Script, OCR-B	
Character Matrix (HxV)	Draft 24 x 9; LQ 24 x 30	
Printing Sizes	5,6,7.5, 8.5,10,12,15,17, & 20 PS	
Characters Per Line	40,48,60,68,80,96,120, 137, & 160 cpl	
Character Sets	EPSON mode One Italic and 18 Character set tables, 15 International Character and LEGAL Set, IBM mode 18 Character set tables	
Bit Image (matrix)	360 x 360 dots per inch	
Easy-Set Operator Panel	Controls over 10 functions including:	
	Font	Factory Preset
	Pitch	High Speed
	Paper Loading	Perforation Cut
	Default Settings	Paper Parking
	Clear Buffer	Top of Form function
Line Feed Time	Approx 65 msec (w/ 1/6 inch line feeding)	
Paper Feed	Path:	Method:
	Rear	Push Tractor (adjustable)
	Front	Friction/Cut Sheet Feeder (opt.)
Paper Specifications	Continuous: 4.0" to 10.0", 60 to 90 g/m ² Single Sheet: 4.0" to 11.7", 41 to 90 g/m ² Copies: Original + 4 non carbon copies Thickness: maximum thickness less than 0.014" (0.35 mm)	
Emulation	Epson LQ-300 w/o color (ESC/P2) IBM Proprinter X24E	
Interface	Centronics parallel, RS-232C Serial	
Buffer	Selectable: 1KB/8KB/22KB (default)/54KB	
Noise Level	55 dBA	
Reliability	8000 hrs MTBF @ 25% printing	
Dimensions	17.1" (W) x 12.8" (D) x 5.5" (H)	
Weight	11.5 lbs.	
Consumables & Accessories	Black Fabric Ribbon (KX-P180) Automatic Single Bin Cut Sheet Feeder (KX-PT12)	